

NEMPAL 710 Heavy Duty Paint Remover

Solvent-Based Paint Stripper

Description



NEMPAL 710 Heavy Duty Paint Remover is a powerful and efficient solution designed to remove paint, coatings, and residues from a wide range of surfaces. Whether it is old, stubborn paint on wood, metal, or masonry, this fast-acting formula penetrates deep to break down and lift paint, varnish, and other coatings effortlessly.

NEMPAL 710 is both effective and easy to use, requiring minimal scrubbing and cleaning. Ideal for renovation projects, DIY enthusiasts, and professionals alike, NEMPAL 710 helps restore surfaces to their original condition, ready for refinishing. Safe for most materials, it provides a clean, smooth base without damaging the underlying surface.

For optimal results, apply directly to the painted area, allow time for the product to work, and simply scrap away the residue. Experience the difference with NEMPAL 710—your go-to solution for fast, reliable paint removal.

Technical Properties

Base Material	: Blend of highly reactive solvent
Appearance	: Clear Liquid
Odor	: Solvent-like
Specific gravity	: ± 1.15
Application Temperature (ambient)	: 5 °C – 40 °C

Applications*

It can be used for removal of enamel, polyurethane, acrylic, some epoxy paints, varnishes, and various other types of coatings applied on various surfaces.

* Users are responsible to carry out test prior to installation to confirm compatibility with actual substrates and work conditions.

Features & Benefits

- Non-Corrosive - won't corrode surfaces
- Fast reacting
- Excellent stripping power
- Ready to use - no mixing required
- Cost effective

Directions for Use

1. Caution: Product may splash when removing inner cap due to pressure buildup in can after storing under hot condition.
2. Apply a thick coat onto the painted surface with a brush.
3. Leave it for 10 minutes to react with the paint.
4. Remove the softened paint with a scraper.
5. In case there is paint residue, apply another coat of paint remover and repeat the process.
6. Close cap after use and store in cool, dry place.

Limitations

- Do not shake or agitate tin cans before use.

Storage, Shelf Life, and Packaging

- Highly flammable, keep away from heat source or naked flames. Store properly in a dry and well-ventilated place with temperature below +30°C.
- Use within 12 months from date of production.
- Packaging:

Content / Pcs	Pcs / Carton
500 g	36
1.0 kg	18

Handling Precautions

Contains dichloromethane and methanol. Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Harmful if swallowed. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. Wash hands, forearms and face thoroughly after handling. IF exposed or concerned: Call a POISON CENTER or doctor. Keep out of reach of children. Use product outdoors whenever possible. If used indoor, open all doors and windows and ventilate the area by using a fan. DO NOT use it in an enclosed area with poor ventilation. Do not shake tin cans before use, allow to release the pressure slowly while removing the cap. For further health and safety information, please refer to the latest Safety Data Sheet.

Disclaimer	The information provided herein reflects our current best knowledge and is offered as guidance for our customers. However, it does not absolve users from thoroughly inspecting all supplies upon receipt. We reserve the right to update product properties as new developments or technical progress arise. Users should verify the recommendations in this TDS through preliminary trials, as certain conditions during processing are beyond our control. This document does not constitute a warranty, expressed or implied, regarding the fitness or suitability of the product for any specific purpose. The company assumes no responsibility for any loss or damage resulting from product use, as variations in processing, working conditions, or workmanship may occur beyond our control.		
For Enquiry	Company: Bond Alike Sdn. Bhd. Email: sales@nempal.com	Address: No. 15, Jalan BP 4/1, Bandar Bukit Puchong, 47120 Puchong, Selangor, Malaysia. Phone: +603-5889 1615	
Document	ID: 100/tds/nempal/710/60/en/25-01	Version 25-01	Last Update: 07 January 2025
